Priefert®

SPECIALTY FINISHED TUBING





BALLED END TUBING

Unique Balled End Tubing features a smooth domed end cap unlike any other in the industry, making it ideal for a wide variety of uses, including fencing, trailers, and specialty fabrication.

NOTCHED END TUBING

Custom Notched End Tubing is designed for a vast assortment of applications, including fencing, trailers, and specialty fabrication. Notched ends allow for an exact fit when joining tubing to help facilitate simplistic and low waste welding.

www.priefertsteel.com

ps_bro_tubing_0724

Priefert®

STEEL TUBING



STANDARD & SPECIALTY TUBING GUIDE

ISO 9001
QMS CERTIFIED



www.priefertsteel.com



ROUND TUBING

Round Tubing is an economical tube that is easy to weld and form, and can be cut-to-length from the mill. It is ideal for a wide variety of applications, including trailers, fencing, agricultural uses, handrails, gates, and more.

Size	Gauge	Length
0.750"	18ga/16ga	CTL
0.840"	14ga/12ga	CTL
1.000"	22ga/20ga/19ga/18ga/16ga/13ga/12ga	CTL
1.050"	22ga/20ga/19ga/18ga/16ga/13ga/12ga	CTL
1.315"	22ga/20ga/19ga/18ga/16ga/14ga/13ga/12ga/11ga	CTL
1.660"	22ga/20ga/19ga/18ga/16ga/14ga/13ga/12ga/11ga/10ga/9ga	CTL
1.900"	20ga/19ga/18ga/16ga/14ga/13ga/12ga/11ga/10ga/9ga	CTL
2.000"	20ga/19ga/18ga/16ga/14ga/13ga/12ga/11ga	CTL
2.375"	16ga/14ga/13ga/12ga/11ga/10ga/9ga/8ga/7ga	CTL
2.875"	14ga/13ga/12ga/11ga/10ga/9ga/8ga/7ga	CTL
3.000"	14ga/13ga/12ga/11ga/10ga/9ga/8ga/7ga/ 1/4"	CTL
3.500"	14ga/13ga/12ga/11ga/10ga/9ga/8ga/7ga/ 1/4"	CTL
4.000"	14ga/13ga/12ga/11ga/10ga/9ga/8ga/7ga/ 1/4"	CTL
4.500"	14ga/13ga/12ga/11ga/10ga/9ga/8ga/7ga/ 1/4"	CTL

Standard Tolerances per ASTM A-513 Type 1 & Type 2
*CR 22ga - 16ga
*HR 16ga - 1/4"
*HRPO 16ga - 1/4"

SQUARE TUBING

Square Tubing is excellent for many uses, including frames, trailers, fencing, carports, steel buildings, and truck beds. This steel shape is easy to weld, cut, form, and machine, and can be cut-to-length from the mill.

Size	Gauge	Length
1.000"	16ga/14ga/13ga/12ga/11ga	CTL
1.250"	14ga/11ga	CTL
1.500"	16ga/14ga/13ga/12ga/11ga	CTL
2.000"	16ga/14ga/13ga/12ga/11ga/ 3/16" / 1/4"	CTL
2.500"	14ga/11ga/ 3/16" / 1/4"	CTL
3.000"	14ga/11ga/ 3/16" / 1/4" / 3/8"	CTL
3.500"	11ga/ 3/16" / 1/4"	CTL
4.000"	14ga/11ga/ 3/16" / 1/4" / 3/8"	CTL

Standard Tolerances per ASTM A-513, A-500 Type 1

RECTANGULAR TUBING

Rectangular Tubing is a welded tube with an internal welded seam. It is designed to meet a variety of applications, which include general fabrication, bridges, buildings, trailers, framework, and fencing.

Size	Gauge	Length
1.00"x2.00"	16ga/14ga/12ga/11ga	CTL
1.00"x3.00"	16ga/14ga/12ga/11ga	CTL
1.50"x3.00"	14ga/11ga	CTL
2.00"x3.00"	11ga/ 3/16" / 1/4"	CTL
2.00"x4.00"	14ga/11ga/ 3/16" / 1/4"	CTL
2.00"x5.00"	11ga/ 3/16" / 1/4"	CTL
2.00"x6.00"	11ga/ 3/16" / 1/4"	CTL
3.00"x4.00"	11ga/ 3/16"	CTL
3.00"x6.00"	3/16" / 1/4"	CTL

Standard Tolerances per ASTM A-513, A-500 Type 1

